



EUROPEAN PRODUCT CATALOGUE



**CRAFTED IN
INDIA TRUSTED
EVERYWHERE**



WHO WE ARE

JK Tyre & Industries Ltd. is a leading Indian tyre manufacturer, ranking amongst the top 19 globally. Since 1977, we have been a trusted partner, providing superior tyre technology and performance across diverse segments – agriculture, industrial, passenger vehicles, and even mining. Our extensive network of 12 manufacturing facilities – 9 in India and 2 in Mexico – produces over 37 million tyres annually. This translates to 37 million opportunities for you to experience exceptional value and optimal performance, every single time.



**TRUCK
BUS RADIAL**



TYRE NOMENCLATURE (TRUCK/BUS RADIAL)

JK TYRE	AXLE POSITION	APPLICATION	EVOLUTION	BENEFIT
J	 DRIVE AND DUMMY AXLE	M Motorway 	X Xtra	M Mileage 
		E Mileage & Load 		D Durability 
		Y Heavy Duty 		F Fuel Saving 
		L Long Haul 		
	 FRONT / UNIVERSAL AXLE	H Regional Haulage 	Future 2X 3X	e Electric Vehicles 
		C Construction 		
		X Urban 		
		O Off Road 		
	 TRAILER AXLE	Z Cross Country 		
		S Sand Cum Highway 		



SIZES	PATTERN											
	JETWAY JUH3+	JETWAY JUH5	JETWAY JUH6	JETWAY JUX+	JETWAY JUL2	JETWAY JUL3	JETWAY JUL4	JETWAY JUM	JETWAY JUM XM2	JETWAY JUC	JETWAY JUC3	
225/70R19.5							✓					
245/70R19.5							✓					
265/70R19.5							✓					
285/70R19.5												
335/80R20												
8.25R20	✓											
9.00R20												
10.00R20	✓									✓		
11.00R20												
12.00R20												
385/55R22.5												
295/60R22.5												
315/60R22.5							✓					
385/65R22.5			✓				✓					
425/65R22.5												
255/70R22.5												
275/70R22.5												
315/70R22.5							✓					
255/80R22.5		✓										
275/80R22.5					✓							
295/80R22.5				✓		✓	✓	✓	✓			
315/80R22.5						✓	✓				✓	
11R22.5		✓				✓				✓		
12R22.5					✓						✓	
13R22.5			✓									
325/95R24												
12.00R24												
												





SIZES	PATTERN										
	JETWAY JUC3+	JETWAY JUC4	JETWAY JUC-XD	JETWAY JUC XM	JETSTEEL JDL3	JETSTEEL JDL3+	JETSTEEL JDL-XM	JETSTEEL JDH	JETSTEEL JDH3	JETSTEEL JDH5+	JETSTEEL JDH6
225/70R19.5						✓					
245/70R19.5						✓					
265/70R19.5			✓								
285/70R19.5						✓					
335/80R20											
8.25R20									✓		
9.00R20								✓			
10.00R20									✓		
11.00R20	✓	✓		✓				✓			
12.00R20		✓									
385/55R22.5											
295/60R22.5					✓						
315/60R22.5					✓						
385/65R22.5		✓									
425/65R22.5		✓									
255/70R22.5											
275/70R22.5											
315/70R22.5					✓						
255/80R22.5							✓				
275/80R22.5								✓			
295/80R22.5				✓	✓		✓			✓	
315/80R22.5		✓			✓						✓
11R22.5								✓		✓	
12R22.5									✓		
13R22.5		✓									
325/95R24		✓									
12.00R24		✓									





SIZES	PATTERN									
	JETSTEEL JDE++	JETSTEEL JDC	JETSTEEL JDC3	JETSTEEL JDC4	JETSTEEL JDC-XD	JETWAY JTH1	JETWAY JTL	JETWAY JUX e	JETWAY JUZ+	JETSTEEL JDO XD
225/70R19.5										
245/70R19.5										
265/70R19.5										
285/70R19.5							✓			
335/80R20									✓	
8.25R20	✓									
9.00R20	✓									
10.00R20	✓		✓							
11.00R20	✓		✓		✓					
12.00R20		✓		✓						✓
385/55R22.5							✓			
295/60R22.5										
315/60R22.5										
385/65R22.5							✓			
425/65R22.5							✓			
255/70R22.5						✓		✓		
275/70R22.5						✓		✓		
315/70R22.5					✓					
255/80R22.5										
275/80R22.5										
295/80R22.5			✓		✓			✓		
315/80R22.5			✓		✓					
11R22.5		✓				✓				
12R22.5			✓		✓					✓
13R22.5		✓		✓						✓
325/95R24										
12.00R24										✓





JETWAY-JUH3+



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Wider shoulder ribs
- ▶ Twisted geometry
- ▶ Unique groove design
- ▶ Construction
- ▶ Superior tread compound

BENEFITS

- ▶ Even wear characteristics and reducing lateral forces
- ▶ Better directional stability
- ▶ Excellent heat dissipation
- ▶ New belt pack for least buzz out & multiple retreads
- ▶ High wear resistant, low RR

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
8.25R20	14	6.5X20	964	230	12	K	136/134	2240	2120	830
8.25R20	16	6.5X20	964	230	12	K	137/135	2300	2180	860
10.00R20	16	7.5X20	1049	278	14	K	146/143	3000	2725	830



JETWAY-JUH5



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Straight groove design
- ▶ Trendy and unique lateral sipe design
- ▶ Higher tread depth
- ▶ Wider tread surface
- ▶ Tread compound

BENEFITS

- ▶ Better vehicle handling
- ▶ Extra traction and improved grip on wet surfaces
- ▶ Extra initial mileage
- ▶ Optimum pressure distribution
- ▶ Better wear characteristics & low RR

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
255/80R22.5	-	7.5 x 22.5	981	253	14.5	J	145/142	3150	2900	900
11R22.5	16	8.25X22.5	1054	282	16.5	L	146/143	3000	2725	830





JETWAY-JUH6



SALIENT FEATURES

- ▶ Wide and high tread depth
- ▶ Wide shoulder rib
- ▶ Zigzag groove with unique lateral sipe
- ▶ Premium tread compound

BENEFITS

- ▶ High initial tread mileage
- ▶ Uniform shoulder wear and even pressure distribution
- ▶ Better traction & grip at wet surface
- ▶ Better wear resistance and cut chip performance

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
385/65R22.5	24	11.75X22.5	1075	385	16	K (L)	164 (158)	5000	-	900
13R22.5	18	9.75X22.5	1121	320	17	K	156/150	4000	3350	875



JETWAY-JUX+



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ 5 straight rib design
- ▶ Wider shoulders
- ▶ Diamond shape stone ejectors
- ▶ Low rolling resistance
- ▶ Superior tread compound

BENEFITS

- ▶ Direction stability and high heat dissipation
- ▶ Uniform wear during turning and cornering
- ▶ Ease in ejection of stone due to diamond geometry
- ▶ Maximum fuel saving
- ▶ High wear resistance

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
295/80R22.5	18	8.25X22.5	1059	298	18.5	J	152/148	3550	3150	850





JETWAY-JUL2



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ 5 rib pattern design
- ▶ Wider shoulder ribs
- ▶ New multiple sipe geometry & micro sipes
- ▶ Multiple stone ejector in the center of grooves
- ▶ Tread compound

BENEFITS

- ▶ Better directional stability and low rolling resistance
- ▶ Uniform wear during cornering and superior grip
- ▶ Better traction in new tyres & to prevent channel/river wear
- ▶ Reduce stone entrapment, resulting in reduced chunking
- ▶ Higher mileage and cooler running

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
275/80R22.5	16	8.25X22.5	1028	279	16	L	149/146	3250	3000	850
12R22.5	16	9.0X22.5	1085	298	16	L	152/148	3550	3150	850



JETWAY-JUL3



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ New multiple 3D sipe geometry & micro sipes
- ▶ Straight ribs
- ▶ Wide shoulder ribs
- ▶ Multiple stone ejector in the center of grooves

BENEFITS

- ▶ Better traction in new tyres & even wear
- ▶ Better directional stability
- ▶ Even wear while cornering
- ▶ Reduce stone entrapment, resulting in reduced chunking

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
295/80R22.5	16	8.25X22.5	1056	298	17.3	M	154/149	3750	3250	850
315/80R22.5	20	9.0X22.5	1080	312	17.3	M	156/150	4000	3350	850
11R22.5	16	8.25X22.5	1056	282	17.3	L	146/143	3000	2725	830





JETWAY-JUL4



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ 5 rib pattern design
- ▶ Wide shoulder ribs
- ▶ Innovative 3D and micro sipe design
- ▶ Twisted flank angles
- ▶ Tread compound

BENEFITS

- ▶ Better directional stability and low rolling resistance
- ▶ Help resist tearing and accelerated wear in high scrub application
- ▶ Improved traction and superior wear characteristics
- ▶ Reduce stone entrapment
- ▶ Higher mileage and cooler running



AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
225/70R19.5	14	6.5X19.5	810	225	13.5	L	128/126	1800	1700	760
245/70R19.5	16	7.5 X19.5	834	245	13.5	M	136/134	2240	2120	830
245/70R19.5	18	7.5 X19.5	834	245	13.5	J	144/142	2800	2650	900
265/70R19.5	16	7.50 X19.5	866	257	13.5	M	140/138	2500	2360	775
265/70R19.5	18	7.50 X19.5	866	257	13.5	K	143/141	2725	2575	850
315/60R22.5	UNDER DEVELOPMENT							-	-	930
385/65R22.5	24	11.75X22.5	-	385	-	K (L)	164 (158)	5000	-	930
315/70R22.5	18	9.00X22.5	1014	312	14	L	156/150	4000	3350	900
295/80R22.5	18	8.25X22.5	UNDER DEVELOPMENT			M	154/149	3750	3250	850
315/80R22.5	20	9.00X22.5	1075	312	14.5	L	156/150	4000	3350	850

JETWAY-JUM



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ 5 straight rib design
- ▶ Wide shoulders
- ▶ Diamond shape stone ejectors
- ▶ New sipe design
- ▶ Special tread compound

BENEFITS

- ▶ Better direction stability and low rolling resistance
- ▶ Better lateral stability
- ▶ Ease in ejection of stone from diamond geometry
- ▶ Arrest initial irregular wear
- ▶ High wear resistance and maximum fuel saving



AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
295/80R22.5	18	8.25X22.5	1052	294	15.3	M	154/149	3750	3250	850

JETWAY JUM XM2



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ 4 rib design with twisted central ribs
- ▶ Wide shoulder ribs
- ▶ Stress relieving sipes
- ▶ Straight groove at shoulder
- ▶ New tread compound

BENEFITS

- ▶ Reduced block shuffling and stone entrapment
- ▶ Better lateral stability
- ▶ Uniform wear
- ▶ Good directional stability
- ▶ Provides low RRC & enhanced mileage



AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
295/80R22.5	18	8.25X22.5	1049	294	16	M	154/149	3750	3250	850

JETWAY-JUC



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Optimized land-sea distribution
- ▶ Conventional radial semi-lug pattern
- ▶ Long pitches with slight bends and lateral grooves
- ▶ Optimum under tread rubber
- ▶ Deep buttress window

BENEFITS

- ▶ Good mileage with smooth wear
- ▶ Premium performance on radial tyres on all wheels
- ▶ Aggressive looks with smooth wear
- ▶ Multiple retreads
- ▶ Better cooling



AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
10.00R20	16	7.5X20	1055	280	16.5	K	146/143	3000	2725	830
11R22.5	16	8.25X22.5	1052	282	16.5	L	148/145	3150	2900	850



JETWAY-JUC3



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Rugged pattern design
- ▶ Wider crown and shoulder ribs
- ▶ Zigzag groove geometry
- ▶ Open buttress design and scooped notch at shoulder
- ▶ Flexed rib support between ribs

BENEFITS

- ▶ Better traction
- ▶ High direction stability and uniform tread wear
- ▶ No stone entrapment
- ▶ Reduced heat development at shoulder
- ▶ Helps in circumferential flexing of ribs

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
315/80R22.5	20	9.00X22.5	1084	312	18	M	156/150	4000	3350	850
315/80R22.5*	20	9.00X22.5	1084	312	18	L	156/150	4000	3350	850
12R22.5	16	9.00X22.5	1086	298	18	L	152/148	3550	3150	850

*Available with side wall protection



JETWAY-JUC3+



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Closed shoulder design
- ▶ Innovative lateral groove design
- ▶ Unique twisted groove geometry
- ▶ Open buttress design and scooped notch at shoulder
- ▶ Exclusive tread compound

BENEFITS

- ▶ Improved handling and stability
- ▶ Provides excellent traction and braking
- ▶ Prevents stone entrapment
- ▶ Reduced heat development at shoulder
- ▶ Superior resistance against cutting and chipping

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
11.00R20	16	8.0X20	1083	290	15.9	K	150/147	3350	2650	830



JETWAY-JUC4



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Rugged pattern design
- ▶ Wider shoulder ribs
- ▶ Robust structural design
- ▶ Open buttress design and scooped notch at shoulder
- ▶ Exclusive tread compound

BENEFITS

- ▶ Better traction
- ▶ High direction stability and uniform tread wear
- ▶ Multiple retreads
- ▶ Reduced heat development
- ▶ Superior resistance against cutting and chipping

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
11.00R20	16	8.0X20	1089	289	17	L	150/146	3350	2650	825
12.00R20	18	8.50X20	1123	313	17	L	154/151	3750	3250	830
315/80R22.5	18	9.00X22.5	1075	312	16	L	156/150	4000	3350	850
13R22.5	18	9.75 X 22.5	1123	320	17	K	156/150	4000	3350	875
325/95R24	22	8.50X24	1225	313	16	K	162/160	4750	4500	850
12.00R24	20	8.50X24	1225	313	16	K	160/156	4500	4000	850



JETWAY-JUC XD



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Wide and deep tread
- ▶ Open shoulder rugged pattern design
- ▶ Rigid circumferential tie bars
- ▶ Specially designed compound

BENEFITS

- ▶ Better pressure distribution & high initial mileage
- ▶ Better traction and heat dissipation
- ▶ Restrict the block shuffle, leading to uniform wear
- ▶ Better cut and chip resistance

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
385/65R22.5	24	11.75X22.5	1077	385	18.2	K (L)	164 (158)	5000	-	900
425/65R22.5	UNDER DEVELOPMENT							-	-	930





JETWAY JUC XM



SALIENT FEATURES

- ▶ Wide shoulder ribs
- ▶ Developed flank angles with zigzag groove
- ▶ Improved version of typical semi lug pattern
- ▶ Extreme block angle

BENEFITS

- ▶ Better directional stability
- ▶ Enhance block rigidity results in uniform wear
- ▶ Making it suitable for both steer & drive application
- ▶ Making it suitable for mixed application

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
11.00R20	16	8.0X20	1087	290	18	K	150/147	3350	2650	830
265/70R19.5	18	7.50 X19.5	870	257	15.8	K	143/141	2725	2575	850
295/80R22.5	18	8.25X22.5	1053	294	17	M	154/149	3750	3250	850



JETSTEEL-JDL3



SALIENT FEATURES

- ▶ Wide tread surface with 6 block design
- ▶ Innovative 3D void generating sipes
- ▶ Twisted block flank surface
- ▶ Interblock tie bars

BENEFITS

- ▶ Superior pressure distribution
- ▶ Prevents irregular wear and improves wet performance throughout the life
- ▶ Preventing stone entrapment and improving casing durability
- ▶ Improved stiffness promoting outstanding driving performance

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
295/60R22.5	18	9.00X22.5	928	293	18.7	L	150/147	3350	2650	900
315/60R22.5	20	9.75X22.5	960	312	16.5	L	152/148	3550	3150	900
315/70R22.5	18	9.00X22.5	1023	312	18	L	154/150	3750	3250	900
295/80R22.5	18	8.25X 22.5	1062	298	20	M	154/149	3750	3250	850
315/80R22.5	20	9.00X22.5	1085	312	18	L	156/150	4000	3350	850



JETSTEEL JDL3+



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Wide tread surface with 6-block unique pattern design
- ▶ Wide center track
- ▶ Unique sipe design
- ▶ Interblock tie bars

BENEFITS

- ▶ Provides superior pressure distribution & Strong traction
- ▶ Good ground contact resulting in smooth wear
- ▶ Improved wet traction and grip
- ▶ Improved stiffness promoting outstanding driving performance

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
225/70R19.5	14	6.5 X19.5	817	225	16.5	L	128/126	1800	1700	760
245/70R19.5	16	7.5 X19.5	841	245	16.5	M	136/134	2240	2120	830
285/70R19.5	UNDER DEVELOPMENT							-	-	930



JETSTEEL-JDL XM



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ 4 block design with wide tread surface
- ▶ High tread depth
- ▶ Wide opening windows
- ▶ Special tread compound

BENEFITS

- ▶ Better pressure distribution
- ▶ Higher initial tread mileage
- ▶ Cooler running in long haulage application
- ▶ Low RRC & high mileage

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
255/80R22.5	-	7.5X22.5	985	253	17	J	145/142	3150	2900	900
295/80R22.5	16	8.25X22.5	1058	294	20	M	154/149	3550	3150	850





JETSTEEL JDH



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ 3 groove block design
- ▶ Wider lateral grooves
- ▶ Wider crown and shoulder blocks
- ▶ Solid block design

BENEFITS

- ▶ Uniform pressure distribution
- ▶ Better traction and braking properties
- ▶ High directional stability and even/smooth wear
- ▶ Excellent mileage at recommended loads

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
9.00R20	16	7.00	1020	258	16.7	K	142/140	2650	2325	830
11.00R20	16	8.00X20	1089	290	19	K	150/147	3350	2650	830
275/80R22.5	16	8.25X22.5	1022	279	17	L	149/146	3250	3000	850
11R22.5	16	8.25X22.5	1062	282	18.5	L	148/145	3150	2900	850



JETSTEEL-JDH3



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ 3 groove block design
- ▶ Wide lateral grooves
- ▶ Wide crown and shoulder blocks
- ▶ Window in shoulder blocks
- ▶ Superior tread compound

BENEFITS

- ▶ Uniform pressure distribution
- ▶ Better traction and braking efficiency
- ▶ High directional stability and even/smooth wear
- ▶ Enables cooler running of tyres
- ▶ Excellent cut and chip resistance

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
8.25R20	14	6.5X20	973	230	16.5	K	136/134	2240	2120	830
8.25R20	16	6.5X20	973	230	16.5	K	137/135	2300	2180	860
10.00R20	16	7.5X20	1056	282	18	K	146/143	3000	2725	830
12R22.5	16	9.0X22.5	1087	298	19	L	152/148	3550	3150	850



JETSTEEL JDH5+



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Robust tread blocks
- ▶ Open shoulder design
- ▶ High tread depth
- ▶ Unique sipe design
- ▶ Special tread compound

BENEFITS

- ▶ Excellent traction, braking and uniform pressure distribution
- ▶ Excellent traction and heat dissipation
- ▶ Higher initial tyre mileage
- ▶ Improved wet traction and grip
- ▶ Excellent abrasion resistance & fuel economy

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
11R22.5	16	8.25X22.5	1065	282	21.5	L	146/143	3000	2725	830



JETSTEEL-JDH6



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ 6 block tread design
- ▶ Wide center blocks
- ▶ Open shoulder design
- ▶ High strength steel belts
- ▶ Special tread compound

BENEFITS

- ▶ Excellent pressure distribution
- ▶ Good ground contact resulting in smooth wear
- ▶ Better traction and cooler running
- ▶ Very good carcass strength
- ▶ Excellent abrasion resistance & fuel economy

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
295/80R22.5	18	8.25X22.5	1070	298	23.5	K	154/149	3750	3250	850
315/80R22.5	20	9.00X22.5	1097	312	23.5	M	156/150	4000	3350	850





JETSTEEL JDE++



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Optimized footprint with robust tread blocks
- ▶ Wider lateral grooves
- ▶ Open shoulder design
- ▶ Superior tread compound
- ▶ Large air envelope

BENEFITS

- ▶ Excellent pressure distribution for all load application
- ▶ Better traction and braking properties
- ▶ Better heat dissipation
- ▶ Excellent cut and chip resistance
- ▶ Extra-load carrying capacity

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
8.25R20	16	6.5X20	979	243	17.2	K	137/135	2300	2180	860
9.00R20	16	7.00X20	1027	258	18	K	142/140	2650	2325	830
10.00R20	16	7.5X20	1066	282	19	K	146/143	3000	2725	830
11.00R20	16	8.0X20	1090	290	20	K	150/147	3350	2650	830



JETSTEEL-JDC



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Robust non-directional tread blocks
- ▶ Open shoulder design
- ▶ Solid tie bars between blocks
- ▶ Higher tread depth

BENEFITS

- ▶ Better vehicle handling, excellent traction in both on/off road conditions
- ▶ Enhanced traction and runs cooler
- ▶ Extra strength and block rigidity
- ▶ Higher mileage

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
12.00R20	18	8.5X20	1128	313	21	K	154/151	3750	3250	830
11R22.5	16	8.25X22.5	1058	282	19	L	148/145	3150	2900	850
13R22.5	18	9.00X22.5	1128	320	21	K	156/150	4000	3350	875



JETSTEEL JDC3



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Wide tread surface with 6 block design
- ▶ Innovative 3D void generating sipes
- ▶ Twisted block flank surface
- ▶ Interblock tie bars

BENEFITS

- ▶ Superior pressure distribution
- ▶ Prevents irregular wear and improves wet performance throughout the life
- ▶ Preventing stone entrapment and improving casing durability
- ▶ Improved stiffness promoting outstanding driving performance

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
10.00R20	16	7.5X20	1069	282	20	K	146/143	3000	2725	830
11.00R20	16	8.0X20	1092	296	20.5	K	150/147	3350	2650	830
295/80R22.5	18	8.25X22.5	1069	298	20	K	152/148	3550	3150	850
315/80R22.5	20	9.00X22.5	1095	312	22.5	K	156/150	4000	3350	850
12R22.5	16	9.0X22.5	1091	298	20.5	L	152/148	3550	3150	850



JETSTEEL-JDC4



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Robust Tread Blocks
- ▶ High Void Ratio
- ▶ High tread depth
- ▶ Trumpet Groove Design at Shoulder
- ▶ Special Tread Compound

BENEFITS

- ▶ Better vehicle handling
- ▶ Excellent traction in both ON & OFF Road conditions
- ▶ Better stability in mud & sledge roads
- ▶ Higher mileage
- ▶ Offers superior self cleaning capability
- ▶ Improved Cut & Chip in Tread area

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
12.00R20	18	8.50X20	1126	313	20	L	154/151	3750	3250	930
13R22.5	18	9.75X22.5	1126	320	20	K	156/150	4000	3350	875





JETSTEEL JDC XD



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Zigzag groove design
- ▶ Solid shoulder tie bar
- ▶ High non-skid depth
- ▶ Special compound

BENEFITS

- ▶ Provide better traction
- ▶ Reduced block shuffling at higher loads
- ▶ Provides high initial mileage
- ▶ High mileage & resistance to cut & chip



AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
11.00R20	16	8X20	1092	290	20.5	K	150/147	3350	2650	830
315/70R22.5	18	9.00X22.5	1029	310	20	L	154/150	3750	3250	900
295/80R22.5	18	9.00X22.5	1060	297	21.7	K	154/149	3750	3250	930
315/80R22.5	18	9.00X22.5	1088	312	21.5	K	156/150	4000	3350	930
315/80R22.5	20	9.00X22.5	1088	312	21.5	K	156/150	4000	3350	930
315/80R22.5	20	9.00X22.5	1088	312	21.5	K	156/150	4000	3350	850
12R22.5	16	9.00X22.5	1093	298	20.5	L	152/148	3550	3150	850

JETWAY-JTH1



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ 5 straight rib pattern
- ▶ Unique groove design
- ▶ Construction design

BENEFITS

- ▶ Better directional stability and low rolling resistance
- ▶ Less stone entrapment
- ▶ High retread factor
- ▶ High initial mileage & low rolling resistance



AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
255/70R22.5	16	7.5X22.5	930	256	13.5	M	140/137	2500	2300	830
275/70R22.5	16	8.25X22.5	960	276	14	L	148/145	3150	2900	900
275/70R22.5	18	8.25X22.5	960	276	14	J	152/148	3550	3150	900
11R22.5	16	8.25X22.5	1047	282	13	L	148/145	3150	2900	850



JETWAY JTL



SALIENT FEATURES

- ▶ 5 straight rib design
- ▶ Twisted groove design
- ▶ Unique sipe design
- ▶ Optimum tread design
- ▶ Specially designed tread compound
- ▶ Better directional stability and low rolling resistance
- ▶ Less stone entrapment
- ▶ Better traction
- ▶ Ensures even wear in trailer axle position
- ▶ High initial mileage and better fuel economy

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
285/70R19.5	UNDER DEVELOPMENT							-	-	930
385/55R22.5	20	12.25X22.5	999	374	14.3	K (L)	160 (158)	4500	-	900
385/65R22.5	24	11.75X22.5	1072	385	15	K (L)	164 (158)	5000	-	900
425/65R22.5	UNDER DEVELOPMENT							-	-	930



JETWAY JUX



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Closely packed center
- ▶ Wider shoulders rib
- ▶ Unique sipe design and pattern
- ▶ Unique noise fence design
- ▶ Robust kerb rib design at buttress

BENEFITS

- ▶ Track for enhanced mileage and energy efficiency
- ▶ Higher lateral stiffness
- ▶ Lower noise
- ▶ Lowering pipe resonance effect
- ▶ Protection against sidewall damages

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
255/70R22.5	16	7.50X22.5	932	255	16	M	140/137	2500	2300	830
255/70R22.5	18	7.50X22.5	932	255	-	M	143/140	2725	2325	900
275/70R22.5	16	8.25X22.5	966	270	18.5	J	150/148	3350	3150	900
275/70R22.5	18	8.25X22.5	966	276	18.5	J	152/148	3550	3150	900
295/80R22.5	18	8.25X22.5	1053	297	18	M	154/149	3750	3250	850





JETWAY JUZ+



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Aggressive block geometry
- ▶ Improved tread
- ▶ Exceptional handling on-road
- ▶ The tyre optimised

BENEFITS

- ▶ Higher block stiffness
- ▶ Robustness
- ▶ Easy and comfort riding
- ▶ For all-terrain and all Position

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
335/80R20	20	10W-20	1032	332	16	K	154/149	3750	3250	800



JETSTEEL JDO XD



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Continuous groove design
- ▶ Open shoulder design
- ▶ Solid tie-bars between blocks
- ▶ Mining tread compound

BENEFITS

- ▶ Good traction in mining application
- ▶ Extra traction in off the road conditions
- ▶ Extra strength and block rigidity
- ▶ Lower tread chipping and very good cut resistance

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
12.00R20	22	8.5X20	1138	314	24	F	156/153	4000	3350	900
12R22.5	20	9.00X22.5	UNDER DEVELOPMENT			L	152/148	3550	3150	850
13R22.5	18	9.00X22.5	1137	320	24.3	K	156/150	4000	3350	875
13R22.5	20	UNDER DEVELOPMENT								
12.00R24	24	8.50X24	1254	313	30	F	164/161	5000	-	930





**LIGHT
TRUCK RADIAL**



SIZES	PATTERN									
	JETWAY JUH5	JETWAY JUL3	JETWAY JUC	JETWAY JUS	JETWAY JUZ	JETSTEEL JDL-XM	JETSTEEL JDH5	JETWAY JUX e	JETSTEEL JDC4	
7.00R16	✓									
7.50R16	✓	✓	✓				✓			
8.25R16	✓	✓					✓			
245/70R17.5	✓					✓		✓		
215/75R17.5		✓	✓				✓	✓	✓	
225/75R17.5		✓					✓	✓		
235/75R17.5	✓		✓				✓	✓	✓	
9.5R17.5		✓							✓	
10R17.5	✓			✓	✓					
										



JETWAY-JUH5



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Straight groove design
- ▶ Trendy and unique lateral sipe design
- ▶ Higher tread depth
- ▶ Wider tread surface
- ▶ Tread compound

BENEFITS

- ▶ Better vehicle handling
- ▶ Extra traction and improved grip on wet surfaces
- ▶ Extra initial mileage
- ▶ Optimum pressure distribution
- ▶ Better wear characteristics and low RR



AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
7.00R16	12	5.5FX16	785	205	10.3	M	115/110	1215	1060	655
7.00R16	14	5.5	782	202	10.3	M	118/113	1320	1150	725
7.50R16	14	6.0GX16	808	216	12	M	122/118	1500	1450	725
8.25R16	14	6.0GX16	852	234	12.5	M	129/127	1850	1750	795
245/70R17.5	16	7.5X17.5	794	248	12.5	M	136/134	2240	2120	850
245/70R17.5	18	7.5 X17.5	794	248	12.5	J	143/141	2725	2575	875
235/75R17.5	14	6.75X17.5	800	234	15	M	132/130	2000	1900	775
235/75R17.5	18	6.75X17.5	800	234	15	J	143/141	2725	2575	865
10R17.5	16	7.5X17.5	862	254	13	M	134/132	2120	2000	800

JETWAY-JUL3



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- New multiple 3D sipe geometry & micro sipes
- Straight ribs
- Wide shoulder ribs
- Multiple stone ejector in the center of grooves

BENEFITS

- Better traction in new tyres & even wear
- Better directional stability
- Even wear while cornering
- Reduce stone entrapment, resulting in reduced chunking



AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
7.50R16	14	6.0GX16	808	216	12	M	122/121	1500	1450	690
7.50R16	16	6.00	809	215	12	M	124/120	1600	1400	795
8.25R16	16	6.0GX16	852	234	12.5	M	129/127	1850	1750	795
215/75R17.5	14	6.0X17.5	775	213	12.5	M	126/124	1700	1600	700
215/75R17.5	16	6.0X17.5	775	213	12.5	M	128/126	1800	1700	750
215/75R17.5*	16	6.0X17.5	775	213	12.5	J	135/133	2180	2060	850
225/75R17.5	14	6.75X17.5	786	224	13.5	M	129/127	1850	1750	725
9.5R17.5	14	6.75X17.5	843	235	13	M	129/127	1850	1750	750
9.5R17.5*	16	6.75X17.5	843	235	13	L	139/137	2430	2300	825
9.5R17.5*	18	6.75X17.5	843	235	13	K	143/141	2725	2575	875

*Available with FRT



JETWAY-JUC



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Optimized land-sea distribution
- ▶ Conventional radial semi-lug pattern
- ▶ Long pitches with slight bends and lateral grooves
- ▶ Optimum under tread rubber
- ▶ Deep buttress window

BENEFITS

- ▶ Good mileage with smooth wear
- ▶ Premium performance on radial tyres on all wheels
- ▶ Aggressive looks with smooth wear
- ▶ Multiple retreads
- ▶ Better cooling



AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
7.50R16	14	6.0G x 16	809	216	12	M	122/121	1500	1450	690
215/75R17.5	16	6.0X17.5	776	213	14	J	135/133	2180	2060	850
235/75R17.5	16	6.75X17.5	801	234	15.7	M	132/130	2000	1900	775

JETWAY-JUS



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Aggressive tread pattern
- ▶ Extracted tread/lug
- ▶ Stepped grooves

BENEFITS

- ▶ Provide extra traction in off-road
- ▶ Improves self cleaning in soft soils
- ▶ Better flotation in sand application



AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
10R17.5	16	7.5X17.5	867	254	15.5	K	134/133	2120	2060	800



JETWAY-JUZ



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Unique tread pattern with dual size tread blocks
- ▶ Higher void ratio
- ▶ Special tread compound

BENEFITS

- ▶ Helps in better traction
- ▶ Better stability in mud and sludge roads
- ▶ Improve wear and cracks



AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
10R17.5	16	7.5X17.5	867	254	15.5	K	134/132	2120	2000	800

JETSTEEL JDL XM



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ 4 block design with wide tread surface
- ▶ Open shoulder design
- ▶ Uniform pressure distribution
- ▶ Unique sipe design
- ▶ Premium blended rubber compound

BENEFITS

- ▶ Better pressure distribution and higher mileage
- ▶ Runs cooler at high speed for longer duration
- ▶ Reduced irregular wear and enhanced mileage
- ▶ Lower rolling resistance



AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
245/70R17.5	16	7.5 X17.5	800	253	14.7	M	136/134	2240	2120	850



JETSTEEL-JDH5



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Robust tread blocks
- ▶ Wide lateral groove
- ▶ High tread depth
- ▶ High strength steel belts
- ▶ Special tread compound

BENEFITS

- ▶ Excellent contact patch
- ▶ Excellent traction and heat dissipation
- ▶ Very good tyre life
- ▶ Very good carcass strength
- ▶ Excellent abrasion resistance and fuel economy

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
7.50R16	16	6.00	813	216	14.5	M	124/120	1600	1400	795
8.25R16	16	6.0GX16	857	234	15	M	129/127	1850	1750	795
215/75R17.5	14	6.0X17.5	782	213	15	M	126/124	1700	1600	700
225/75R17.5	14	6.75X17.5	792	224	15.5	M	129/127	1850	1750	725
235/75R17.5	14	6.75X17.5	805	235	16.5	M	132/130	2000	1900	775



JETWAY JUX



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Closely packed center
- ▶ Wider shoulders rib
- ▶ Unique sipe design and pattern
- ▶ Unique noise fence design
- ▶ Robust kerb rib design at buttress

BENEFITS

- ▶ Track for enhanced mileage and energy efficiency
- ▶ Higher lateral stiffness
- ▶ Lower noise
- ▶ Lowering pipe resonance effect
- ▶ Protection against sidewall damages

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
245/70R17.5	16	7.50X17.5	799	250	14.5	M	136/134	2240	2120	850
215/75R17.5	14	6.0X17.5	775	213	12.5	M	126/124	1700	1600	700
225/75R17.5	14	6.75X17.5	787	224	14	M	129/127	1850	1750	725
235/75R17.5	14	6.75X17.5	799	235	14	M	132/130	2000	1900	775



JETSTEEL JDC4



RECOMMENDED FITMENT POSITION

SALIENT FEATURES

- ▶ Robust Tread Blocks
- ▶ High Void Ratio
- ▶ High tread depth
- ▶ Trumpet Groove Design at Shoulder
- ▶ Special Tread Compound

BENEFITS

- ▶ Better vehicle handling
- ▶ Excellent traction in both ON & OFF Road conditions
- ▶ Better stability in mud & sledge roads
- ▶ Higher mileage
- ▶ Offers superior self cleaning capability
- ▶ Improved Cut & Chip in Tread area

AVAILABLE SIZES:

TYRE SIZE	PLY RATING	RIM WIDTH (INCH)	UNLOADED INFLATED TYRE DIMENSIONS			SPEED (KMPH)	LOAD INDEX	MAX. LOAD CARRYING CAPACITY		
			OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)			SINGLE (KGS)	DUAL (KGS)	IP (KPA)
215/75R17.5	16	6.0X17.5	777	213	15.5	J	135/133	2180	2060	850
235/75R17.5	16	6.75X17.5	801	234	16.5	M	132/130	2000	1900	775
9.5R17.5	18	6.75X17.5	848	235	16.5	K	143/141	2725	2575	875



NOTES

[illegible]

JK TYRE & INDUSTRIES LTD.

CORPORATE OFFICE

Patriot House, 3, Bahadur Shah Zafar Marg, New Delhi - 110002

Ph.: +91 011-66001112, 011-66001122

Fax: 02952-232018 Ph: 02952-233400 / 233000

Website: www.jktyre.com Email ID: tyre-exports@jkmail.com

Follow us on:

